Free and Total Chlorine Handheld Colorimeters



Easier to use and more accurate than chemical test kits

EPA approved DPD method

±0.03 ppm ±3% of reading accuracy 0.01 ppm resolution (250 points for free chlorine, 350 for total chlorine)

Large, easy to read digits

Auto shut off

Dedicated to a single parameter

Designed to work with HANNA's powder reagents

Uses 10 mL glass cuvettes

Small size, big convenience

The Checker®HC easily fits into the palm of your hand or pocket

Use for quick and accurate on the spot analysis

Single button operation: zero and measure

Operated by a single AAA battery

Ideal for:

Swimming pools and spas, fruit and vegetable sanitation, disinfection, drinking water and quality control checks

disinfectant. The monitoring of chlorine is crucial in applications such as swimming pools and spas, fruit and vegetable sanitation, disinfection and drinking water. By monitoring this crucial parameter, serious health and safety risks can be avoided.

Chlorine is the most common water

The HANNA HI 711 and HI 701 Checker® HC's bridge the gap between simple chemical test kits and professional instrumentation. Chemical test kits are not very accurate and only give 5 to 10 points resolution while professional instrumentation can cost hundreds of dollars and can be time consuming to calibrate and maintain. The HANNA HI 711 and HI 701 Checker®HC's are accurate and affordable.

These Checker®HC portable handheld colorimeters feature a resolution of 0.01 ppm (250 points for free chlorine, 350 for total chlorine) and ±0.03 ppm (mg/L) ±3% of reading accuracy. They also use an EPA approved DPD method.

The contoured style of these Checker®HC's fit in your palm and pocket perfectly and the large LCD is easy to read. The auto shutoff feature assures the battery life will not be drained if you forget to turn it off.

The HI 711 and HI 701 Checker®HC's are extremely simple to use. First, zero the instrument with your water sample. Next, add the reagent. Last, place the vial into the Checker®HC, press the button and read the results. It's that easy.

ORDERING INFORMATION

HI 711 Checker®HC is supplied with sample cuvettes with caps (2), powder reagents for Total Chlorine (5), battery and instructions.

HI 701 Checker® HC is supplied with sample cuvettes with caps (2), powder reagents for Free Chlorine (5), battery and instructions.

REAGENTS AND STANDARDS

HI 711-25	Reagents for 25 tests (Total Cl ₂)	
HI 701-25	Reagents for 25 tests (Free Cl ₂)	
HI 711-11	Calibration checking set	
	0.00 and 1.00 ppm (Total Cl ₂)	
HI 701-11	Calibration checking set	
	0.00 and 1.00 ppm (Free Cl ₂)	

ACCESSORIES

HI 731318	Cuvette cleaning cloth (4)
HI 731321	Glass cuvettes (4)
HI 731225	Caps for cuvettes (4)
HI 93703-50	Cuvette cleaning solution, 230 mL

SPECIFICATIONS	HI 711 (Total Chlorine)	HI 701 (Free Chlorine)	
Range	0.00 to 3.50 ppm (mg/L)	0.00 to 2.50 ppm (mg/L)	
Resolution	0.01 ppn	0.01 ppm (mg/L)	
Accuracy @ 25°C/77°F	tource LED @ 525 nm Silicon photocell Inment O to 50°C (32 to 122°F); RH max 95% non-condensing Type (1) 1.5V AAA Iff after two minutes of non-use and ten seconds after reading Sions 81.5 x 61 x 37.5 mm (3.2 x 2.4 x 1.5") the first formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x 2.4 x 1.5) formula of the seconds after reading (3.2 x		
Light Source			
Light Detector			
Environment			
Battery Type			
Auto-off			
Dimensions			
Weight			
Method			
·	·		

